



4299-T8

# Pump Protector

FOR WINTERIZING PUMPS

*Foam-in Corrosion Protection*

For All Seasonally Operated Pumps

No Special Rinse Required

U.S.D.A. Approved

**DANGER:**  
EXTREMELY  
FLAMMABLE LIQUID  
AND VAPOR  
VAPOR HARMFUL  
CONTENTS UNDER  
PRESSURE

- KEEP OUT OF REACH
  - OF CHILDREN.
  - See back panel for
  - additional precautionary
  - statements.
- 
- **FOR PROFESSIONAL**
  - **USE ONLY**

### Foam-in Shut Down Corrosion Protection for All Types of Pumps

Any pump that is shut down and drained part of the time should be safeguarded with Aerosol Pump Protector. Pumps used in cooling towers, swimming pools, and vacation homes, auxiliary pumps, marine and industrial pumps can develop corrosion deposits on the impeller and other close-tolerance areas during shut down, causing the pump to bind. Aerosol Pump Protector prevents this corrosion and lubricates the pump so that it starts right up every time! Pump Protector is water soluble and will not cause any foaming problem when the pump is started. If the pump is used for drinking water, flush it thoroughly by running water off a few minutes before placing the pump back in service.

#### DIRECTIONS FOR USE:

This product must be used in accordance to the following directions by HVACR professionals only.

#### PUMP SHUT-DOWN

1. DRAIN the pump.
2. SHAKE can well before using.
3. ATTACH plastic extension tube (located inside cap). Be careful not to press side ways while attaching tube.
4. INVERT can, placing tubing into drain opening of pump.
5. ACTIVATE can by pressing nozzle sideways until empty. One can of Aerosol Pump Protector provides sufficient material for coating

#### DANGER

Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes serious eye damage.

#### Precautionary statement

Do not spray on an open flame or other ignition source. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye protection/face protection. **IF SWALLOWED:** Immediately call a POISON CENTRE/doctor. Do NOT induce vomiting. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTRE/doctor. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Store in a well-ventilated place. Dispose of contents/container in accordance with local/regional/national/international regulations.

most pumps; more will be needed for large pumps.

6. RUN pump a few seconds or rotate shaft by hand to coat all surfaces.

#### PUMP START-UP

Flush pump thoroughly with water before bringing it back to service.

**CONTAINS (CAS NO):** Heavy Paraffinic Oil (64742-65-0), Propylene Glycol (57-55-6), Petroleum gases, liquefied, sweetened (68476-86-8), Octadecanoic acid (57-11-4), Ethanol,2,2',2''-nitrilotris-(102-71-6), Alcohols,C12-14--secondary,ethoxylated(84133-50-6),Alcohols,C12-14, ethoxylated (68439-50-9).

**NOTICE:** Reports have associated repeated and prolonged occupational overexposure to solvents with brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Ensure fresh air entry during application. If you experience eye watering, headaches or dizziness or if air monitoring demonstrates vapor/mist levels are above applicable limits, wear an appropriate, properly fitted respirator (NIOSH approved) during and after application. Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes, skin and clothing.



Manufactured for:  
Nu-Calgon  
2611 Schuetz Rd.  
St. Louis, MO 63043

Customer Service: 800-554-5499  
Chemical Emergency: 800-424-9300  
www.nucalgon.com

Made in Canada. (818) Calgon is a licensed trade name.



NET WT. 10 OZ. (284 GRAMS)