SAFETY DATA SHEET



1. Identification

Product identifier Vacuum Pump Oil (4383-07, 4383-24, 4383-34, 4383-01)

Other means of identification Not available.

Recommended use Lubricating vacuum pumps

Recommended restrictions None known.

Manufacturer information Nu-Calgon

2611 Schuetz Road St. Louis, MO 63043 US

Phone: 314-469-7000 / 800-554-5499

Emergency Phone: 1-800-424-9300 (CHEMTREC)

Supplier See above.

2. Hazard identification

Physical hazards Not classified.

Health hazards Not classified.

Environmental hazards Not classified.

WHMIS 2015 defined hazards Not classified

Label elements

Hazard symbol None.
Signal word None.

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

WHMIS 2015: Health Hazard(s)

not otherwise classified

(HHNOC)

None known

None known

WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC)

Hazard(s) not otherwise

classified (HNOC)

136

None known.

Supplemental information Not applicable.

3. Composition/Information on ingredients

Mixture

Chemical nameCommon name and synonymsCAS number%Distillates (petroleum), hydrotreated heavy paraffinic64742-54-780-100*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments US GHS: The exact percentage (concentration) of composition has been withheld as a trade

secret in accordance with paragraph (i) of §1910.1200.

*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a

trade secret.

4. First-aid measures

InhalationIf symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.Skin contactFlush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.Eye contactFlush with cool water. Remove contact lenses, if applicable, and continue flushing. Obtain medical

attention if irritation persists.

Ingestion Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean

Direct contact with eyes may cause temporary irritation.

forward to reduce risk of aspiration. Never give anything by mouth if victim is unconscious or is

convulsing.

protect themselves.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed
General information

Treat patient symptomatically. Symptoms may be delayed.

Ensure that medical personnel are aware of the material(s) involved and take precautions to

5. Fire-fighting measures

Suitable extinguishing media

Large Fires: Water spray. Water fog. Foam.

Unsuitable extinguishing

the chemical

Do not c

Small Fires: Dry chemical powder. Carbon dioxide. Foam. Water spray. Do not use water jet as an extinguisher, as this will spread the fire.

media
Specific hazards arising from

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire-fighting equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods
General fire hazards

Use standard firefighting procedures and consider the hazards of other involved materials.

Seneral fire hazards

No unusual fire or explosion hazards noted.

Hazardous combustion products

May include and are not limited to: Oxides of carbon.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep out of low areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Stop the flow of material, if this is without risk.

Large Spills: Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material. Keep out of reach of children. Store in a closed container away from incompatible materials.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/Personal protection

Occupational exposure limits

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)

Components	туре	value	Form	
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	STEL	10 mg/m3	Mist.	
	TWA	5 mg/m3	Mist.	

Good general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels ividual protection measures, such as personal protective equipment Eye/face protection Bkin protection Hand protection Hand protection Other Respiratory protection Where exposure guideline levels may be exceeded, use an approvace Respirator should be selected by and used under the direction of a professional following requirements found in OSHA's respirator stars.	Mist. Form				
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), hydrotreated spears (Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA 5 mg/m3 Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) B hour 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type value to the ingredient(s). Good general ventilation (typically 10 air changes per hour) should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below received engineering to the matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below received engineering to the matched to conditions. If applicable, use process enclose or other engineering controls to mainta					
Inydrotreated heavy paraffinic (CAS 64742-54-7) Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and scomponents Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) INVA Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) 8 hour 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA 5 mg/m3 logical limit values Ook general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels worked to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels worked to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne l	Inhalahla frastian				
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA 5 mg/m3	Inhalable fraction.				
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA 5 mg/m3 Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) 8 hour 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), STEL 10 mg/m3 hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), STEL 10 mg/m3 hydrotreated heavy paraffinic (CAS 64742-54-7) TWA 5 mg/m3 Rogical limit values or of the ingredient(s). Good general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels widual protection Hand protection Hand protection Hand protection Cother Wear safety glasses with side shields (or goggles). Wear suitable protective clothing. Where exposure guideline levels may be exceeded, use an approve Respiratory protection of the professional following requirements found in OSHA's respirator stan CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z8 CAN/CSA-Z94.4 and ANSI's standard for respiratory	afety) Form				
Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) Components Type Value Distillates (petroleum), 15 minute 10 mg/m3 hydrotreated heavy paraffinic (CAS 64742-54-7) 8 hour 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value Distillates (petroleum), TWA 5 mg/m3 hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), STEL 10 mg/m3 hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), STEL 10 mg/m3 hydrotreated heavy paraffinic (CAS 64742-54-7) TWA 5 mg/m3 Rogical limit values Ood general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels invidual protection measures, such as personal protective equipment Eyefface protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Hand protection Wear suitable protective clothing. Where exposure guideline levels may be exceeded, use an approv Respiratory should be selected by and used under the direction of professional following requirements found in OSHA's respirator state of professional following requirements found in OSHA's respirator state of professional following requirements found in OSHA's respirator state of professional following requirements found in OSHA's resp	Mist.				
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) 8 hour 5 mg/m3	Mist.				
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) 8 hour 5 mg/m3 US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 647742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA 5 mg/m3 No biological exposure limits noted for the ingredient(s). Good general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels brown or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels widual protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Umpervious gloves. Confirm with reputable supplier first. Wear suitable protective clothing. Wear suitable protective clothing. Where exposure guideline levels may be exceeded, use an approve Respiratory stond in OSHA's respirator state CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z86)					
hydrotreated heavy paraffinic (CAS 64742-54-7) US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA STEL 10 mg/m3 No biological exposure limits noted for the ingredient(s). Good general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels below rece exposure limits have not been established, maintain airborne levels invidual protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Umpervious gloves. Confirm with reputable supplier first. Wear suitable protective clothing. Wear suitable protective clothing. Where exposure guideline levels may be exceeded, use an approve Respirator should be selected by and used under the direction of a professional following requirements found in OSHA's respirator state CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z86)					
US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) Components Type Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA S mg/m3 Rogical limit values No biological exposure limits noted for the ingredient(s). Good general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below recover exposure limits have not been established, maintain airborne levels widual protection measures, such as personal protective equipment Eye/face protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Hand protection Other Wear suitable protective clothing. Where exposure guideline levels may be exceeded, use an approve Respiratory protection of a professional following requirements found in OSHA's respirator stat CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z8)					
Components Type Simple					
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA 5 mg/m3 No biological exposure limits noted for the ingredient(s). TWA 5 mg/m3 logical limit values oropriate engineering attrols Cood general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels fividual protection measures, such as personal protective equipment Eye/face protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Wear suitable protective clothing. Wear suitable protective clothing. Where exposure guideline levels may be exceeded, use an approvent Respiratory protection of a professional following requirements found in OSHA's respirator stat CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z86)					
hydrotreated heavy paraffinic (CAS 64742-54-7) US. ACGIH Threshold Limit Values Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA 5 mg/m3 Rogical limit values Rocopriate engineering about the first of the ingredient (s). Good general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels dividual protection measures, such as personal protective equipment Eye/face protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Wear suitable protective clothing. Respiratory protection Where exposure guideline levels may be exceeded, use an approve Respiratory should be selected by and used under the direction of a professional following requirements found in OSHA's respirator stat CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z8)	Form				
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)	Mist.				
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) US. NIOSH: Pocket Guide to Chemical Hazards Components Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA TWA TWA Type Value Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA TWA TWA TWA TWA TWA TWA TW					
US. NIOSH: Pocket Guide to Chemical Hazards Components Type Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA TWA TWA TWA TWA TWA TWA TW	Form				
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA 5 mg/m3 Propriate engineering antrols Trols Good general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels ividual protection measures, such as personal protective equipment Eye/face protection Hand protection Hand protection Other Respiratory protection Wear safety glasses with side shields (or goggles). Where exposure guideline levels may be exceeded, use an approvent Respirator should be selected by and used under the direction of a professional following requirements found in OSHA's respirator stat CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (28)	Inhalable fraction.				
Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7) TWA 5 mg/m3 logical limit values oropriate engineering htrols Good general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels ividual protection measures, such as personal protective equipment Eye/face protection Bair protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Other Wear suitable protective clothing. Where exposure guideline levels may be exceeded, use an approve Respiratory should be selected by and used under the direction of a professional following requirements found in OSHA's respirator stat CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z8)					
hydrotreated heavy paraffinic (CAS 64742-54-7) TWA 5 mg/m3 logical limit values Propriate engineering Introls Good general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels ividual protection measures, such as personal protective equipment Eye/face protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Other Wear suitable protective clothing. Wear suitable protective clothing. Where exposure guideline levels may be exceeded, use an approve Respirator should be selected by and used under the direction of a professional following requirements found in OSHA's respirator stat CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z8)	Form				
logical limit values Propriate engineering Atrols Good general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels ividual protection measures, such as personal protective equipment Eye/face protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Other Wear suitable protective clothing. Where exposure guideline levels may be exceeded, use an approve Respirator should be selected by and used under the direction of a professional following requirements found in OSHA's respirator stat CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z8)	Mist.				
Good general ventilation (typically 10 air changes per hour) should should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below reconstituted in the protection measures, such as personal protective equipment. Eye/face protection Bair protection Hand protection Hand protection Other Respiratory protection Respiratory protection Where exposure guideline levels may be exceeded, use an approvance approached by and used under the direction of a professional following requirements found in OSHA's respirator stat CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z8)	Mist.				
should be matched to conditions. If applicable, use process enclose or other engineering controls to maintain airborne levels below rece exposure limits have not been established, maintain airborne levels ividual protection measures, such as personal protective equipment Eye/face protection Wear safety glasses with side shields (or goggles). Skin protection Hand protection Other Wear suitable protective clothing. Where exposure guideline levels may be exceeded, use an approve Respirator should be selected by and used under the direction of a professional following requirements found in OSHA's respirator stat CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z8)					
Eye/face protection Skin protection Hand protection Other Respiratory protection Wear suitable protective clothing. Where exposure guideline levels may be exceeded, use an approve Respirator should be selected by and used under the direction of a professional following requirements found in OSHA's respirator stat CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (28)	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.				
Skin protection Hand protection Other Respiratory protection Where exposure guideline levels may be exceeded, use an approve Respirator should be selected by and used under the direction of a professional following requirements found in OSHA's respirator state CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (28)					
Hand protection Other Wear suitable protective clothing. Where exposure guideline levels may be exceeded, use an approve Respirator should be selected by and used under the direction of a professional following requirements found in OSHA's respirator state CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z8)					
Other Wear suitable protective clothing. Respiratory protection Where exposure guideline levels may be exceeded, use an approve Respirator should be selected by and used under the direction of a professional following requirements found in OSHA's respirator state CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z8)					
Respiratory protection Where exposure guideline levels may be exceeded, use an approven Respirator should be selected by and used under the direction of a professional following requirements found in OSHA's respirator state CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z8)					
Respirator should be selected by and used under the direction of a professional following requirements found in OSHA's respirator state CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z8)					
	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).				
	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.				
9. Physical and chemical properties					

Physical stateLiquid.FormLiquid.ColorColorless

Odor Slight hydrocarbon
Odor threshold Not available.

pH Not available
Melting point/freezing point Not available.

Initial boiling point and boiling > 536 °F (> 280 °C)

range

Pour point 5 °F (-15 °C)

Specific gravity Not available.

Partition coefficient > 6

(n-octanol/water)

Flash point 437.0 °F (225.0 °C) Cleveland Open Cup

Evaporation rate Not available
Flammability (solid, gas) Not applicable.
Upper/lower flammability or explosive limits

Explosive limit - lower (%) 1 Explosive limit - lower (%) 1

temperature

Explosive limit - upper (%) 10
Explosive limit - upper (%) 10

temperature

Vapor pressureNot available.Vapor density> 1 (Air = 1)Relative density $0.87 \ @ 15^{\circ}$ CSolubility(ies)Not available.

Auto-ignition temperature > 608 °F (> 320 °C) Not available

Decomposition temperatureNot available. **Viscosity**40 - 46 cSt @ 40°C

Other information

Density 870 kg/m3 @ 15°C

10. Stability and reactivity

Reactivity This product may react with strong oxidizing agents.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Chemical stability Material is stable under normal conditions.

Conditions to avoid Avoid temperatures exceeding the flash point. Extremes of temperature and direct sunlight.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

May include and are not limited to: Oxides of carbon.

11. Toxicological information

Routes of exposure Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

IngestionMay cause stomach distress, nausea or vomiting.InhalationNo adverse effects due to inhalation are expected.

Skin contact Repeated or prolonged skin exposure may cause acne/folliculitus.

Eye contact Direct contact with eyes may cause temporary irritation.

Symptoms related to the Direct contact with eyes may cause temporary irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Information on toxicological effects

xicological characteristics

Acute toxicity

Components Species Test Results

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

Acute Dermal

LD50 Rabbit > 5000 mg/kg, 24 Hours, ECHA

> 2000 mg/kg, 24 Hours, ECHA

Inhalation

LC50 Rat > 5.5 mg/L, 4 Hours, ECHA

> 5.3 mg/L, 4 Hours, ECHA > 5.2 mg/L, 4 Hours, ECHA

Oral

LD50 Rat > 5000 mg/kg, ECHA

> 2000 mg/kg, ECHA

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Exposure minutesNot available.Erythema valueNot available.Oedema valueNot available.

Serious eye damage/eye

Direct contact with eyes may cause temporary irritation.

irritation

Corneal opacity value Not available.

Iris lesion value Not available.

Conjunctival reddening Not available.

value

Conjunctival oedema value Not available.

Recover days Not available.

Respiratory or skin sensitization

Respiratory sensitization Not available.

Skin sensitization This product is not expected to cause skin sensitization.

Mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Contains < 3% (w/w) DMSO-extract

IARC Monographs. Overall Evaluation of Carcinogenicity

Distillates (petroleum), hydrotreated heavy paraffinic Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity

(CAS 64742-54-7) to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not listed.

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Teratogenicity Not available.

Specific target organ toxicity - Not classified.

single exposure

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard Not available.

Chronic effectsThe finished product is not expected to have chronic health effects.

12. Ecological information

Ecotoxicity See below

Ecotoxicological data

Components Species Test Results

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

Crustacea EC50 Daphnia 1000 mg/L, 48 Hours

Persistence and degradability This product is not readily biodegradable.

Bioaccumulative potential Bioaccumulation potential.

Mobility in soilNot available.Mobility in generalNot available.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is

emptied.

14. Transport information

Transport of Dangerous Goods (TDG) Proof of Classification

Classification Method: Classified as per Part 2, Sections 2.1 - 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.

U.S. Department of Transportation (DOT)

Not regulated as dangerous goods.

Transportation of Dangerous Goods (TDG - Canada)

Not regulated as dangerous goods.

15. Regulatory information

Canadian federal regulations

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions

Not applicable

US federal regulations

This product is NOT known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

All components of this material are on the TSCA Inventory.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely

hazardous substance

SARA 313 (TRI reporting) Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations

US - California Hazardous Substances (Director's): Listed substance

Distillates (petroleum), hydrotreated heavy paraffinic

Listed.

(CAS 64742-54-7)

US - Minnesota Haz Subs: Listed substance

Distillates (petroleum), hydrotreated heavy paraffinic Listed.

(CAS 64742-54-7)

US - Texas Effects Screening Levels: Listed substance

Distillates (petroleum), hydrotreated heavy paraffinic Listed. (CAS 64742-54-7)

US. Massachusetts RTK - Substance List

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

US. Rhode Island RTK

Distillates (petroleum), hydrotreated heavy paraffinic (CAS 64742-54-7)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other information







Disclaimer

Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date 21-October-2022

Version # 0

Effective date 21-October-2022

Prepared by Nu-Calgon Technical Service Phone: (314) 469-7000