

**FOR USE BY HVACR PROFESSIONALS ONLY**

EcoPure R-600a is non-odorized and meets AHRI 700 Standard.

Always follow OEM guidelines and refrigerant best practices.

**DIRECTIONS FOR USE:** Read and understand all warnings and directions before use. The product is extremely flammable; take all necessary precautions during use.

1. Wear protective gear, use hydrocarbon gas monitor, and reaffirm no ignition sources.
2. For accurate system charging, use Nu-Calgon's EcoPure Charging System (4175-11) or Assembly (4175-10).
3. Pull vacuum through suction service port and isolate system to ensure it's leak free.
4. Always charge through the low side of system. Never expose EcoPure canister to high side pressure.
5. Invert cylinder for liquid refrigerant charging. Purge hose, tare scale, slowly charge to OEM specification. If necessary, briefly cycle system to fully charge. Do NOT overcharge.

**WARNING:** Protect from sunlight. Do not expose to heat or store at temperatures above 120°F. Do not store in parked vehicles where temperatures can exceed 120°F. Do not puncture or incinerate canister.



**DANGER**

Extremely flammable gas. Contains refrigerated gas; may cause cryogenic burns or injury. May displace oxygen and cause rapid suffocation.

**PREVENTION:** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Use only outdoors or in a well-ventilated area. Wear cold insulating gloves and either face shield or eye protection. Wear respiratory protection.

**RESPONSE:** Leaking gas fire: Do not extinguish, unless leak can be stopped safely. In case of leakage, eliminate all ignition sources. Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical attention.

**STORAGE:** Store in a well-ventilated place.

**DISPOSAL:** Dispose of container in accordance with local, regional, national and international regulations.

**KEEP AWAY FROM CHILDREN.**

**NON-ODORIZED** liquefied flammable compressed gas – a leak will not be detected by smell.

Use in accordance with the Safety Data Sheet (SDS). Never fill this canister with any other material.

4175-31

**Nu-Calgon**



**R-600a**  
Refrigerant Grade Isobutane

99.5% Pure

Resealable Cannister




Isobutane  
UN 1969  
CAS#75-28-5

DOT 2Q M1119

Nu-Calgon  
2611 Schuetz Rd.  
St. Louis, MO 63043  
Customer Service: 800-554-5499  
Chemical Emergency: 800-424-9300  
www.nucalgon.com  
(0123) Calgon is a licensed trade name.

THIS END UP  
WHEN NOT  
IN USE

THIS END UP  
FOR LIQUID  
CHARGING



Net Wt. 10.6 oz. (300g)