

1. Product and Company Identification

Product identifier	Pump Protector 4299-T8
Other means of identification	Not available
Recommended use	Protectant
Recommended restrictions	None known.
Manufacturer information	Nu-Calgon 2611 Schuetz Road St. Louis, MO 63043 US Phone: 314-469-7000 / 800-554-5499 Emergency Phone: 1-800-424-9300 (CHEMTREC)
Supplier	See above.

2. Hazards Identification

Physical hazards	Flammable aerosols	Category 1
	Gases under pressure	Liquefied gas
Health hazards	Serious eye damage/eye irritation	Category 1
	Aspiration hazard	Category 1
Environmental hazards	Not classified.	
WHMIS 2015 defined hazards	Not classified	
Label elements		



Signal word Danger

Hazard statement Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes serious eye damage.

Precautionary statement

Prevention	Do not spray on an open flame or other ignition source. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye protection/face protection.
Response	IF SWALLOWED: Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
Storage	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store locked up. Store in a well-ventilated place.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.

WHMIS 2015: Health Hazard(s) not otherwise classified (HHNOC) None known

WHMIS 2015: Physical Hazard(s) not otherwise classified (PHNOC) None known

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information None.

3. Composition/Information on Ingredients

Mixture

Chemical name	Common name and synonyms	CAS number	%
1,2-Propanediol		57-55-6	1-5*
Alcohols C12-14 ethoxylated		68439-50-9	0.1-1*
Alcohols, C12-14-secondary, ethoxylated		84133-50-6	1-5*

Chemical name	Common name and synonyms	CAS number	%
Distillates (petroleum), solvent-dewaxed heavy paraffin		64742-65-0	15-40*
Ethanol, 2,2',2"-nitritoltris-		102-71-6	1-5*
Octadecanoic acid		57-11-4	1-5*
Petroleum gases, liquefied, sweetened		68476-86-8	10-30*

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments US GHS: The exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200.
*CANADA GHS: The exact percentage (concentration) of composition has been withheld as a trade secret.

4. First Aid Measures

Inhalation	If symptoms develop move victim to fresh air. If symptoms persist, obtain medical attention.
Skin contact	Flush with cool water. Wash with soap and water. Obtain medical attention if irritation persists.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
Ingestion	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. Do NOT induce vomiting.
Most important symptoms/effects, acute and delayed	Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Symptoms may be delayed.
General information	If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Avoid contact with eyes and skin. Keep out of reach of children.

5. Fire Fighting Measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).
Unsuitable extinguishing media	Not available.
Specific hazards arising from the chemical	Contents under pressure. Pressurized container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Not available.
Fire-fighting equipment/instructions	In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out. In the event of fire and/or explosion do not breathe fumes.
General fire hazards	Extremely flammable aerosol. Contents under pressure. Pressurized container may explode when exposed to heat or flame.
Hazardous combustion products	May include and are not limited to: Oxides of carbon. Oxides of sulfur.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe gas. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
--	---

Methods and materials for containment and cleaning up

Refer to attached safety data sheets and/or instructions for use. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Do not discharge into lakes, streams, ponds or public waters.

7. Handling and Storage

Precautions for safe handling

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not smoke while using or until sprayed surface is thoroughly dry. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Close valve after each use and when empty. Protect cylinders from physical damage; do not drag, roll, slide, or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Do not re-use empty containers. Do not breathe gas. Do not get in eyes, on skin, or on clothing. When using, do not eat, drink or smoke. Use only in well-ventilated areas. Avoid prolonged exposure. Wear appropriate personal protective equipment. Wash thoroughly after handling. Use good industrial hygiene practices in handling this material.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122 °F. Do not handle or store near an open flame, heat or other sources of ignition. Do not puncture, incinerate or crush. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS). Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over. Stored containers should be periodically checked for general condition and leakage. Keep out of reach of children.

8. Exposure Controls/Personal Protection

Occupational exposure limits**Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2)**

Components	Type	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	STEL	10 mg/m ³	Mist.
Ethanol, 2,2',2''-nitrotris- (CAS 102-71-6)	TWA	5 mg/m ³	Mist.
	TWA	5 mg/m ³	
Octadecanoic acid (CAS 57-11-4)	TWA	10 mg/m ³	

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Type	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	TWA	1 mg/m ³	Mist.
Ethanol, 2,2',2''-nitrotris- (CAS 102-71-6)	TWA	5 mg/m ³	
	TWA	5 mg/m ³	
Octadecanoic acid (CAS 57-11-4)	TWA	10 mg/m ³	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	TWA	5 mg/m ³	Inhalable fraction.
Ethanol, 2,2',2''-nitrotris- (CAS 102-71-6)	TWA	5 mg/m ³	
	TWA	5 mg/m ³	
Octadecanoic acid (CAS 57-11-4)	TWA	3 mg/m ³	Respirable fraction.

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Type	Value	Form
		10 mg/m3	Inhalable fraction.

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	Type	Value	Form
1,2-Propanediol (CAS 57-55-6)	TWA	155 mg/m3	Vapor and aerosol.
		10 mg/m3	Aerosol.
		50 ppm	Vapor and aerosol.
Ethanol, 2,2',2''-nitrotris- (CAS 102-71-6)	TWA	3.1 mg/m3	
		0.5 ppm	
Octadecanoic acid (CAS 57-11-4)	TWA	10 mg/m3	

Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment)

Components	Type	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Ethanol, 2,2',2''-nitrotris- (CAS 102-71-6)	TWA	5 mg/m3	

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	TWA	5 mg/m3	Inhalable fraction.
Ethanol, 2,2',2''-nitrotris- (CAS 102-71-6)	TWA	5 mg/m3	
Octadecanoic acid (CAS 57-11-4)	TWA	3 mg/m3	Respirable fraction.
		10 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)	Ceiling	1800 mg/m3	
	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.

US. AIHA Workplace Environmental Exposure Level (WEEL) Guides

Components	Type	Value	Form
1,2-Propanediol (CAS 57-55-6)	TWA	10 mg/m3	Aerosol.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Ensure adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection	
Hand protection	Impervious gloves. Confirm with reputable supplier first.
Other	Wear suitable protective clothing. Use of an impervious apron is recommended. As required by employer code.
Respiratory protection	Where exposure guideline levels may be exceeded, use an approved NIOSH respirator. Respirator should be selected by and used under the direction of a trained health and safety professional following requirements found in OSHA's respirator standard (29 CFR 1910.134), CAN/CSA-Z94.4 and ANSI's standard for respiratory protection (Z88.2).
Thermal hazards	Not applicable.
General hygiene considerations	When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not eat or drink.

9. Physical and Chemical Properties

Appearance	Clear
Physical state	Gas.
Form	Aerosol.
Color	Colorless
Odor	Characteristic
Odor threshold	Not available.
pH	8 - 9
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Pour point	Not available.
Specific gravity	0.85 - 0.89
Partition coefficient (n-octanol/water)	Not available.
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	55 - 65 psig @ 21°C
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Heat of combustion	Level 1
Oxidizing properties	Not oxidizing.
VOC (Weight %)	26.32

10. Stability and Reactivity

Reactivity	This product may react with strong oxidizing agents.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Chemical stability	Material is stable under normal conditions.
Conditions to avoid	Do not mix with other chemicals.

Incompatible materials
Hazardous decomposition products

Strong oxidizing agents.
May include and are not limited to: Oxides of carbon. Oxides of nitrogen.

11. Toxicological Information

Routes of exposure Eye, Skin contact, Inhalation, Ingestion.

Information on likely routes of exposure

Ingestion Droplets of the product aspirated into the lungs through ingestion or vomiting may cause a serious chemical pneumonia. May cause stomach distress, nausea or vomiting.

Inhalation Prolonged inhalation may be harmful.

Skin contact Prolonged or repeated exposure may cause liver and kidney damage. These effects have not been observed in humans.

Eye contact Causes serious eye damage.

Symptoms related to the physical, chemical and toxicological characteristics Aspiration may cause pulmonary edema and pneumonitis. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result.

Information on toxicological effects

Acute toxicity May be fatal if swallowed and enters airways.

Components

1,2-Propanediol (CAS 57-55-6)

Acute

Dermal

LD50

Species

Rabbit

Test Results

> 2000 mg/kg, 24 Hours, ECHA
20800 mg/kg, Millipore

Inhalation

LC50

Rabbit

> 317042 mg/m³, 2 Hours, ECHA

Oral

LD50

Dog

19 g/kg

Guinea pig

19700 mg/kg, ECHA

18.4 g/kg

Mouse

24900 mg/kg, ECHA

23900 mg/kg, HSDB

23.9 g/kg

Rabbit

22.8 g/kg, CCOHS

18 g/kg

Rat

19.4 - 36 g/kg, Millipore

22000 mg/kg, ECHA

21 g/kg, CCOHS

Alcohols C12-14 ethoxylated (CAS 68439-50-9)

Acute

Dermal

LD50

Rabbit

2700 mg/kg

2000 mg/kg, 24 Hours

Rat

> 2000 mg/kg, 24 Hours

Inhalation

LC50

Not available

Rat

> 100 mg/m³, 6 Hours

> 1.6 mg/L, 4 Hours

Oral

LD50

Rat

> 2000 mg/kg

9800 mg/kg

Components	Species	Test Results
Alcohols, C12-14-secondary, ethoxylated (CAS 84133-50-6)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Not available	
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 5000 mg/kg, 24 Hours, ECHA > 2000 mg/kg, 24 Hours, ECHA
<i>Inhalation</i>		
LC50	Rat	< 5.7 mg/L, 4 Hours, ECHA > 5.5 mg/L, 4 Hours, ECHA > 5.3 mg/L, 4 Hours, ECHA > 5.2 mg/L, 4 Hours, ECHA > 4 mg/L, 4 Hours, ECHA > 3.9 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 5000 mg/kg, ECHA > 2000 mg/kg, ECHA 5000 mg/kg, ECHA
Ethanol, 2,2',2''-nitritotris- (CAS 102-71-6)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 20000 mg/kg, HSDB > 2000 mg/kg, ECHA
<i>Inhalation</i>		
LC50	Not available	
<i>Oral</i>		
LD50	Guinea pig Mouse Rat	5300 mg/kg, HSDB 5846 mg/kg, TCI America 5000 mg/kg, EMD Millipore 6400 mg/kg, ECHA 8 g/kg, HSDB
Octadecanoic acid (CAS 57-11-4)		
Acute		
<i>Dermal</i>		
LD50	Rabbit	> 2000 mg/kg, 24 Hours, ECHA 5000 mg/kg, LOLI, CCOHS
<i>Inhalation</i>		
LC50	Rat	> 0.2 mg/L, 4 Hours, ECHA
<i>Oral</i>		
LD50	Rat	> 6000 mg/kg, ECHA > 5000 mg/kg, ECHA > 2000 mg/kg, ECHA 5000 mg/kg, CCOHS 4.6 g/kg, HSDB

Components	Species	Test Results
Petroleum gases, liquefied, sweetened (CAS 68476-86-8)		
Acute		
<i>Dermal</i>		
LD50	Not available	
<i>Inhalation</i>		
LC50	Mouse	539600 ppm, 120 Minutes, ECHA 520400 ppm, 120 Minutes, ECHA 1237 mg/L, 120 Minutes, ECHA 57 %, 120 Minutes, ECHA 52 %, 120 Minutes, ECHA
	Rat	> 800000 ppm, 10 Minutes, ECHA 1442738 mg/m3, 10 Minutes, ECHA 1354944 mg/m3, 10 Minutes, ECHA 570000 ppm, 10 Minutes, ECHA 1443 mg/L, 10 Minutes, ECHA 1355 mg/L, 10 Minutes, ECHA
<i>Oral</i>		
LD50	Not available	
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.	
Exposure minutes	Not available.	
Erythema value	Not available.	
Oedema value	Not available.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Corneal opacity value	Not available.	
Iris lesion value	Not available.	
Conjunctival reddening value	Not available.	
Conjunctival oedema value	Not available.	
Recover days	Not available.	
Respiratory or skin sensitization		
Canada - Alberta OELs: Irritant		
Ethanol, 2,2',2''-nitrilotris-	(CAS 102-71-6)	Irritant
Octadecanoic acid	(CAS 57-11-4)	Irritant
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin sensitization.	
Mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	See below.	
Canada - Manitoba OELs: carcinogenicity		
MINERAL OIL, EXCLUDING METAL WORKING FLUIDS, SUSPECTED HUMAN CARCINOGEN, POORLY AND MILDLY REFINED (CAS 64742-65-0)		
IARC Monographs. Overall Evaluation of Carcinogenicity		
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)		Volume 33, Supplement 7 - 3 Not classifiable as to carcinogenicity to humans.
Ethanol, 2,2',2''-nitrilotris- (CAS 102-71-6)		Volume 77 - 3 Not classifiable as to carcinogenicity to humans.
US NTP Report on Carcinogens: Known carcinogen		
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)		Known To Be Human Carcinogen.
US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)		
Not listed.		
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Teratogenicity	Not available.	
Specific target organ toxicity - single exposure	Not classified.	

Specific target organ toxicity - repeated exposure	Not available.
Aspiration hazard	May be fatal if swallowed and enters airways.
Chronic effects	May be harmful if absorbed through skin.

12. Ecological Information

Ecotoxicity	See below		
Ecotoxicological data Components		Species	Test Results
1,2-Propanediol (CAS 57-55-6)			
Crustacea	EC50	Daphnia	10000 mg/L, 48 Hours
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	> 10000 mg/L, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	710 mg/L, 96 hours
Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)			
Crustacea	EC50	Daphnia	1000 mg/L, 48 Hours
Ethanol, 2,2',2"-nitritoltris- (CAS 102-71-6)			
Algae	IC50	Algae	216 mg/L, 72 Hours
Aquatic			
Crustacea	EC50	Water flea (Ceriodaphnia dubia)	565.2 - 658.3 mg/L, 48 hours
Fish	LC50	Fathead minnow (Pimephales promelas)	10610 - 13010 mg/L, 96 hours
Persistence and degradability	No data is available on the degradability of this product.		
Bioaccumulative potential			
Mobility in soil	No data available.		
Mobility in general	Not available.		
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation)		

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.

14. Transport Information

Transport of Dangerous Goods (TDG) Proof of Classification	Classification Method: Classified as per Part 2, Sections 2.1 – 2.8 of the Transportation of Dangerous Goods Regulations. If applicable, the technical name and the classification of the product will appear below.
General	Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure that containers are firmly secured. Ensure cylinder valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted. Ensure valve protection device (where provided) is correctly fitted. Ensure adequate ventilation. Ensure compliance with applicable regulations.
U.S. Department of Transportation (DOT)	
Basic shipping requirements:	
UN number	UN1950
Proper shipping name	Aerosols, flammable, (each not exceeding 1 L capacity)
Hazard class	Limited Quantity - US
Special provisions	N82
Packaging exceptions	306

Packaging non bulk None

Packaging bulk None

Transportation of Dangerous Goods (TDG - Canada)

Basic shipping requirements:

UN number UN1950

Proper shipping name AEROSOLS, flammable

Hazard class Limited Quantity - Canada

Special provisions 80, 107

Packaging exceptions <1L - Limited Quantity

DOT; TDG



15. Regulatory Information

Canadian federal regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

WHMIS 2015 Exemptions Not applicable

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

All components of this material are on the TSCA Inventory.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - Yes
Reactivity Hazard - No

SARA 302 Extremely hazardous substance No

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)
Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

US state regulations See below

US - California Hazardous Substances (Director's): Listed substance

Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.

US - Minnesota Haz Subs: Listed substance

1,2-Propanediol (CAS 57-55-6) Listed.

Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.
 Ethanol, 2,2',2''-nitrilotris- (CAS 102-71-6) Listed.
 Octadecanoic acid (CAS 57-11-4) Listed.

US - New Jersey RTK - Substances: Listed substance

1,2-Propanediol (CAS 57-55-6)
 Ethanol, 2,2',2''-nitrilotris- (CAS 102-71-6)

US - Texas Effects Screening Levels Hazard Data: Simple asphyxiant

Petroleum gases, liquefied, sweetened (CAS 68476-86-8)

US - Texas Effects Screening Levels: Listed substance

1,2-Propanediol (CAS 57-55-6) Listed.
 Alcohols C12-14 ethoxylated (CAS 68439-50-9) Listed.
 Alcohols, C12-14-secondary, ethoxylated (CAS 84133-50-6) Listed.
 Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0) Listed.
 Ethanol, 2,2',2''-nitrilotris- (CAS 102-71-6) Listed.
 Octadecanoic acid (CAS 57-11-4) Listed.
 Petroleum gases, liquefied, sweetened (CAS 68476-86-8) Listed.

US - Massachusetts RTK - Substance List

Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)
 Ethanol, 2,2',2''-nitrilotris- (CAS 102-71-6)

US - New Jersey Worker and Community Right-to-Know Act

Not regulated.

US - Pennsylvania Worker and Community Right-to-Know Law

1,2-Propanediol (CAS 57-55-6)
 Ethanol, 2,2',2''-nitrilotris- (CAS 102-71-6)

US - Rhode Island RTK

1,2-Propanediol (CAS 57-55-6)
 Distillates (petroleum), solvent-dewaxed heavy paraffin (CAS 64742-65-0)
 Ethanol, 2,2',2''-nitrilotris- (CAS 102-71-6)

US. California Proposition 65

Not Listed.

Inventory status


Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

16. Other Information

LEGEND	
Severe	4
Serious	3
Moderate	2
Slight	1
Minimal	0

HEALTH	/ 2
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available. Information contained herein was obtained from sources considered technically accurate and reliable. While every effort has been made to ensure full disclosure of product hazards, in some cases data is not available and is so stated. Since conditions of actual product use are beyond control of the supplier, it is assumed that users of this material have been fully trained according to the requirements of all applicable legislation and regulatory instruments. No warranty, expressed or implied, is made and supplier will not be liable for any losses, injuries or consequential damages which may result from the use of or reliance on any information contained in this document.

Issue date

24-August-2024

Version #

01

Effective date

24-August-2024

Prepared by

Nu-Calgon Technical Service Phone: (314) 469-7000

Other information

For an updated SDS, please contact the supplier/manufacturer listed on the first page of the document.